



# STRONG MODUL 766 BT

**Vebe Floorcoverings bv**  
 Sisalstraat 105, 8281JK  
 Genemuiden, The Netherlands  
 T +31 (0)88 825 11 00  
 E info@vebe.net  
 W www.vebe.net

## TECHNICAL SPECIFICATIONS

Manufacturing process	Needlefelt		ISO 2424
Surface aspect	Flat		ISO 2424
Fibre composition	70% Polypropylene (PP) / 30% Polyamide 6 (PA6)		
Backing	BT		ISO 2424
Width	50x50 cm		
Total fibre weight of use surface	450 g/m <sup>2</sup>		
Total weight	4140 g/m <sup>2</sup>	± 15%	ISO 8543
Total height	6,5 mm	+15% / -10%	ISO 1765
Flammability	Bfl-s1		EN 13501-1
Overall use class	Class 33 - commercial heavy		EN ISO 10874
Luxury class	LC1		EN 1307
Castor chair suitability	Yes, permanent use		ISO 4918
Colour fastness to light	≥ 5		ISO 105-B02
Colour fastness to rubbing, wet and dry	≥ 4		ISO 105-X12
Colour fastness to water	≥ 4		ISO 105-E01
Electrostatic charging	< 2 kV		ISO 6356
Impact sound protection ΔLW	20 dB		ISO 10140
Acoustical sound absorption	125 Hz 250 Hz 500 Hz 1000 Hz 2000 Hz 4000 Hz 0,00 αs 0,03 αs 0,06 αs 0,13 αs 0,30 αs 0,31 αs		ISO 354
Evaluated sound absorptions grade	15 αW		ISO 11654
Thermal resistance	0,07 m <sup>2</sup> K/W (0,7 TOG)		ISO 8302
Slip resistance	DS (> 0,30)		EN 13893
GUT PRODIS-ID	803DB22A		www.pro-dis.info



V4  
 2026-02-04

Strong Modul 766 BT is manufactured in compliance with ISO 9001:2015 and ISO 14001:2015 certified processes. DISCLAIMER: Vebe Floorcoverings B.V. reserves the right to alter technical specifications without prior notice. All technical specifications are subject to normal manufacturing tolerances. VEBE floorcoverings must be installed following the installation instructions and industry standards, with regular maintenance carried out as recommended.